

96" LAZER Z[®] X-SERIES

**UNMATCHED PERFORMANCE.
MAXIMUM COMFORT AND PRODUCTIVITY.
LEGENDARY DURABILITY.**



Exmark has launched the new 96-inch Lazer Z X-Series model, its largest, most powerful gasoline-powered commercial zero-turn mower. Capable of cutting up to nine acres per hour, the 96-inch Lazer Z X-Series provides the increased productivity necessary to get jobs done more quickly and profitably.

FEATURES:

- Equipped with Kohler® ECV980 EFI engine with electronic throttle body.
- 96-inch UltraCut™ Rear Discharge deck with flex wings. Finish cut baffles come installed.
- Equipped with the next-generation RED Technology.
- Two Exmark® exclusive Parker unitized 16cc pump and 18.9 cu inch wheel motor systems for increased torque.
- Ground speeds up to 10.5 mph.
- Electric over hydraulic deck lift.



ENGINE PROTECTION

A reduction of operating temperatures is provided by an external oil cooler and an engine hood designed to screen intake air coming into the engine. This provides an ample supply of cool, clean air, while reducing the potential for debris build-up around cooling fins.



96" ULTRACUT REAR DISCHARGE WITH FLEX WINGS

A welded 7-gauge, high strength low alloy steel deck shell along with maintenance-free, sealed and non-greasable spindles makes this deck durable and among one of the strongest in the industry. The wings flex 20-degrees up and 15-degrees down. For easy transport and trailering, the wings fold-up to 72.5-inches wide at a 3-inch cut height.



HYDRO-DRIVE SYSTEM

The gas-powered Lazer Z features a rear cast belly and fully reinforced tubular frame that's formed and welded from 7-gauge, high-strength steel. This all adds up to a mower that delivers superior strength, improved traction and unmatched durability.

The mowers landscape professionals trust 2 to 1.*

exmark.com

*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



LAZER Z[®]

X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X L X H)
LZX980EKC96RW0	ECV980 Kohler EFI RED Equipped	96"	UltraCut Rear Discharge w/ flex wings	2200 lbs.	101.2" x 95.8" x 72.5"



POWER COMPONENTS

Engine – ECV980 Kohler Command EFI engine with electronic throttle body. Governed to 3,650 rpm.

Air Filter – Heavy-duty canister air filtration system drawing through pre-screen.

Drive System – Two Exmark® exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components. 16cc pumps and 18.9 cubic inch motors.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection from 0–10.5 mph (16.9 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

PTO Engagement – MagStop Electromagnetic 250-ft-lbs clutch with spot brake.

Fuel Capacity – High-capacity, 12-gallon (45.4-L), single fuel tank with single fill location.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

Rollover Protection System (ROPS) – 2-post foldable ROPS standard with seat belt and latch.

Quick Deck Lift – Standard; electric over hydraulic.

DECK

Style – Full-floating UltraCut Rear Discharge deck. Finish cut baffles installed.

Deck Construction – 7-gauge high strength alloy top that is formed and welded, with 7-gauge high strength alloy side skirt

Widths Available – 96" (244 cm).

Cutting Height – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

Blade Spindles – No maintenance, sealed and non-greasable spindles; Double-Row ORS bearings on top and bottom; 7.75"-diameter cutter housing with 25mm diameter spindle shaft and splined blade driver.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Welded heavy-duty 1.5" x 3" x 3/16" tubular steel with cast rear belly for engine, hood protection and to provide proper machine balance for improved drivability and stability.

Steering and Motion Control – Hydraulically dampened twin levers, adjust fore and aft, also adjustable to 2-height positions. Adjustable dampers (3-positions) to customize drive responsiveness.

Casters – .50" thick caster yoke arm.

Front Caster Tires – 13 x 6.5-6 smooth tread, semi-pneumatic.

Drive Tires – 24 x 12.0-12, 4-ply Turf Master.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated disc brake.

Seat Comfort – Deluxe, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

Onboard Intelligence – Equipped with Next-Generation RED technology.

Electrical – 12-volt battery with 40-amp alternator.

Standard Features – Fuel gauge, console storage compartment and cup holder.

ACCESSORIES & OPTIONS

12-Volt Power Adapter, Jack, Jack Mount Receiver, LED Flasher Kit, LED Light Kit, Rear Discharge Baffle Kit, Rear Discharge Anti-Scalp Non-Marking Bumper, Slow Moving Sign Kit and Sun Shade.



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020.